



CCVZ 3502 - TOP DISCHARGE ONLY

Dimensions (MM)

DUCT CONNECTIONS	
INLET	OUTLET*
H x G	E x F

* DIMENSIONS FOR LOW AMBIENT DAMPER FITTED AS STANDARD (FLANGED CONNECTION)

NB

- 1) Size 351 has fan speed control instead of damper
- 2) Top discharge available on request.
- 3) Sizes 351- 801 only have one fan outlet

CCVZ	A	B	C	D	E	F	G	H	I	J	K	WEIGHT (KG)
351	937	750	1020	301	335	278	500	804	71.5	62	-	180
401	937	750	1020	218	500	310	500	804	71.5	62	170	187
501	1087	750	1020	293	500	310	500	905	91	91	170	230
701	1130	800	1250	315	500	310	770	905	147	78	170	245
721	1130	800	1250	315	500	310	770	905	147	78	170	255
751	1130	800	1250	315	500	310	770	905	147	78	170	270
801	1130	800	1250	315	500	310	770	905	147	78	170	273
1001	1700	870	1250	250	1200	310	875	1400	150	150	170	365
1201	1700	870	1250	250	1200	310	875	1400	150	150	170	375
1002	1700	870	1250	250	1200	310	870	1400	150	150	170	360
1402	1700	870	1250	250	1200	310	870	1400	150	150	170	518
1502	1700	870	1250	250	1200	310	870	1400	150	150	170	536
2002	2150	980	1362	275	1600	310	918	1850	150	150	170	611
2302	2150	980	1362	275	1600	310	918	1850	150	150	170	620
2402	2150	980	1362	275	1600	310	918	1850	150	150	170	636
3002	2800	1050	1722	450	1900	320	1161	2472	164	164	180	1025
3502	2800	1050	1722	450	1900	320	1362	2472	164	164	180	1110

SECTION 1.

**Air Cooled Condensing Unit - Ductable - Cooling Only
Models CCVZ 351 - 3502**