

CW CASSETTE SERIES



UK CAPACITY DATA

RATED AT	COOLING	HEATING
ENTERING AIR	22°C DB, 16°C WB	22°C DB
ENT/LVG WATER	6/12°C	80/60°C

SYSTEM	<i>EUROVENT</i>	UK CAPACITY DATA			MODEL	AIR FLOW (M ³ /S)	CHILLED WATER		ELECTRICAL DATA	
	COOLING	COOLING		HEATING			@ UK CONDITIONS			
	TOTAL (KW)	TOTAL (KW)	SENS (KW)	LTHW/ELEC (KW)			FLOW RATE (L/S)	WATER P D (KPa)	SUPPLY	NOM RUN AMPS
TWO PIPE	2.40	1.22	1.22	-	CW200C	0.183	0.048	5.00	240.1.50	0.33
	4.00	2.67	2.17	-	CW300C	0.204	0.106	5.00	240.1.50	0.29
	4.70	3.09	2.57	-	CW400C	0.250	0.123	4.00	240.1.50	0.46
	6.30	3.88	3.33	-	CW500C	0.272	0.157	9.00	240.1.50	0.32
	8.67	5.25	4.79	-	CW701C	0.402	0.210	5.00	240.1.50	0.91
TWO PIPE + E/HTR	4.70	3.09	2.57	2.50 (1Ph)	CW400A	0.250	0.123	4.00	240.1.50	10.87 *
	8.67	5.25	4.79	3.00 (1Ph)	CW701A	0.402	0.210	5.00	240.1.50	13.41 *
FOUR PIPE	4.10	1.86	1.85	5.89	CW400D	0.250	0.074	1.00	240.1.50	0.48
	7.61	4.18	4.05	14.75	CW701D	0.402	0.170	7.00	240.1.50	0.92

* Includes electric heater

Contact Hushon (UK) Limited on 023 92 324335 or Sales@hushonuk.co.uk for selection assistance

Note: ALL information is subject to change without prior notification – check all details before final selection