



## Quad-Split 4-Way Cassette Indoor Unit

CODE			200	230
<b>Performance</b>				
<b>Indoor Unit 1</b>		<b>RAV-</b>	<b>RM561UTP-E</b>	<b>RM801UTP-E</b>
<b>Indoor Unit 2</b>		<b>RAV-</b>	<b>RM561UTP-E</b>	<b>RM801UTP-E</b>
<b>Indoor Unit 3</b>		<b>RAV-</b>	<b>RM561UTP-E</b>	<b>RM801UTP-E</b>
<b>Indoor Unit 4</b>		<b>RAV-</b>	<b>RM561UTP-E</b>	<b>RM801UTP-E</b>
<b>Outdoor Unit</b>		<b>RAV-</b>	<b>SM2246AT8-E</b>	<b>SM2806AT8-E</b>
Nominal	Cooling Capacity	kW	20.0	23.0
	Heating Capacity	kW	22.4	27.0
	EER/COP	W/W	3.21/3.85	2.81/3.48
UK	Cooling Total/Sensible	kW	19.30/15.30	22.20/17.00
	Heating	kW	17.63	14.63
Cooling EN14825	Range Min. - Max.	kW	9.8 - 22.4	9.8 - 27.0
	Power Input	kW	6.24	8.19
	Pdesign	kW	20.0	23.5
	SEER/Energy Efficiency Class (or ηsc %)		6.82/159.0	6.28/248.2
	Seasonal Energy Consumption	kWh/a	-	-
Heating EN14825	Range Min. - Max.	kW	9.8 - 25.0	9.8 - 31.5
	Power Input	kW	5.82	7.76
	Pdesign	kW	20.0	22.0
	SCOP/Energy Efficiency Class (or ηsc(A) %)		4.05/159.0	3.90/153.0
	Seasonal Energy Consumption	kWh/a	-	-
<b>Indoor Data</b>				
Air Flow	High - Medium - Low	l/s	292 - 242 - 217	342 - 267 - 225
	High - Medium - Low	m <sup>3</sup> /h	1050 - 870 - 780	1230 - 960 - 810
Sound	Pressure High - Medium - Low	dB(A)	32 - 29 - 28	35 - 31 - 28
	Power High - Medium - Low	dB(A)	47 - 44 - 43	50 - 46 - 43
Unit	Height x Width x Depth	mm	256 x 840 x 840	256 x 840 x 840
	Weight	kg	20	20
Panel	Height x Width x Depth	mm	30 x 950 x 950	30 x 950 x 950
	Weight RBC-UM31PGP(W)-E	kg	4.2	4.2
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8
	Height Difference Indoor To Indoor	m	±0.5	±0.5
	Outdoor Connection To Distributor (gas - liquid)	inch	5/8 - 3/8	1/2 - 1/4
	Sub Branch Line To Indoor (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8
	Sub Branch Line To Second Dist. (gas - liquid)	inch	1-1/8 - 1/2	1-1/8 - 1/2
	Max. Subtractive Separation Between Indoors	m	6	6
	Max. Length Main Distributor To Furthest Indoor	m	20	20
	Max. Distance From Second Distributor To Indoors	m	10	10
	Drain Pipe Connection OD/ID	mm	VP25	VP25
Power Cable	Indoor to Indoor		2 core + earth	2 core + earth
Remote Controller			RBC-AMT32E	RBC-AMT32E
<b>Outdoor Data</b>				
Operating Range	Cooling/Heating	°C	46 to -15/15 to -20	46 to -15/15 to -20
Air Flow	High	m <sup>3</sup> /h - l/s	8000 - 2222	9000 - 2500
Sound	Pressure High Cooling/Heating	dB(A)	56/57	57/58
	Power High Cooling/Heating	dB(A)	72/74	74/75
Unit	Height x Width x Depth	mm	1540 x 900 x 320	1540 x 900 x 320
	Weight	kg	134	134
Pipe Connection	Flare Connections (gas - liquid)	inch	1-1/8 - 1/2	1-1/8 - 1/2
	Min.-Max. Length	m	5-100	5-100
	Maximum Height Difference	m	±30	±30
	Drain Port Connection	mm	16	16
Refrigerant	Gas - Base Charge	kg	R410A - 5.9	R410A - 5.9
	Additional Charge Main Liquid Side	g/m	80	80
	Additional Charge Second Dist. Liquid Side	g/m	40	40
	Additional Charge Sub Liquid Side	g/m	20	40
Run Current	Maximum	A	10.09	13.24
Power Cable	Outdoor to Header Indoor		3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	380-415/3/50-16	380-415/3/50-20

For Features and Accessories, please refer to the individual single-split system units.