



Twin-Split Compact Cassette Indoor Unit

CODE			50	67	95	95
Performance						
Indoor Unit 1		RAV-	RM301MUT-E	RM401MUT-E	RM561MUT-E	RM561MUT-E
Indoor Unit 2		RAV-	RM301MUT-E	RM401MUT-E	RM561MUT-E	RM561MUT-E
Outdoor Unit		RAV-	GM561ATP-E	GM801ATP-E	GM1101ATP-E	GM1101AT8P-E
Nominal	Cooling Capacity	kW	5.0	6.7	9.5	9.5
	Heating Capacity	kW	5.3	7.7	11.2	11.2
	EER/COP	W/W	3.21/3.9	3.02/3.62	3.17/3.44	3.17/3.44
UK	Cooling Total/Sensible	kW	4.80/3.50	6.90/5.58	9.60/7.00	9.60/7.00
	Heating	kW	3.79	5.12	7.30	7.30
Cooling EN14825	Range Min. - Max.	kW	1.5 - 5.6	1.5 - 8.0	3.0 - 11.2	3.0 - 11.2
	Power Input	kW	1.56	2.22	3.00	3.00
	Pdesign	kW	5.00	6.70	9.50	9.50
	SEER/Energy Efficiency Class		5.69/A+	-*	5.50/A	5.50/A
	Seasonal Energy Consumption	kWh/a	319	-*	604	604
Heating EN14825	Range Min. - Max.	kW	1.5 - 6.3	1.5 - 9.0	3.0 - 13.0	3.0 - 13.0
	Power Input	kW	1.36	2.13	3.26	3.26
	Pdesign	kW	2.80	5.10	7.40	7.40
	SCOP/Energy Efficiency Class		4.37/A+	-*	4.02/A+	4.02/A+
	Seasonal Energy Consumption	kWh/a	1279	-*	2576	2576
Indoor Data						
Air Flow	High - Medium - Low	l/s	178 - 144 - 122	183 - 153 - 130	222 - 187 - 152	222 - 187 - 152
	High - Medium - Low	m³/h	640 - 520 - 440	660 - 552 - 468	798 - 672 - 546	798 - 672 - 546
Sound	Pressure High - Medium - Low	dB(A)	38 - 36 - 30	41 - 36 - 32	44 - 39 - 35	44 - 39 - 35
	Power High - Medium - Low	dB(A)	53 - 51 - 45	56 - 51 - 47	59 - 54 - 50	59 - 54 - 50
Unit	Height x Width x Depth	mm	256 x 575 x 575	256 x 575 x 575	256 x 575 x 575	256 x 575 x 575
	Weight	kg	15	15	15	15
Panel	Height x Width x Depth	mm	12 x 620 x 620	12 x 620 x 620	12 x 620 x 620	27 x 700 x 700
	Weight RBC-UM21PG(W)-E	kg	2.5	2.5	2.5	2.5
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Height Difference Indoor To Indoor	m	±0.5	±0.5	±0.5	±0.5
	Outdoor Connection To Distributor (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Sub Branch Line To Indoor (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Max. Subtractive Separation Between Indoors	m	5	5	10	10
	Max. Length Distributor To Furthest Indoor	m	10	10	15	15
	Drain Pipe Connection OD/ID	mm	VP26/20	VP26/20	VP26/20	VP26/20
Power Cable	Indoor to Indoor		2 core + earth	2 core + earth	2 core + earth	2 core + earth
Remote Controller			RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
Outdoor Data						
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15
Air Flow	High	m³/h - l/s	2400 - 667	2700 - 750	4080 - 1133	4080 - 1133
Sound	Pressure High Cooling/Heating	dB(A)	46/48	48/52	54/57	55/57
	Power High Cooling/Heating	dB(A)	63/65	65/69	70/74	70/74
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	890 x 900 x 320	890 x 900 x 320
	Weight	kg	40	44	68	69
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Min.-Max. Length	m	5-30	5-30	5-50	5-50
	Maximum Height Difference	m	±30	±30	±30	±30
	Drain Port Connection	mm	16	16	16	16
Refrigerant	Gas - Base Charge	kg	R32 - 0.9	R32 - 1.3	R32 - 2.1	R32 - 2.1
	Additional Charge Main Liquid Side	g/m	20	35	35	35
	Additional Charge Sub Liquid Side	g/m	20	20	20	20
Run Current	Maximum	A	7.31	10.40	15.44	5.15
Power Cable	Outdoor to Header Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16	220-240/1/50-16	220-240/1/50-20	380-415/3/50-10
* Waiting for published data.						

For Features and Accessories, please refer to the individual single-split system units.