



Multi-Split Shorai High-Wall Indoor Unit

CODE			27	37	45	60	71
Performance							
Indoor Unit		RAS-	B10PKVSG-E	B13PKVSG-E	B16PKVSG-E	B22PKVSG-E	B24PKVSG-E
Capacity Code			10	13	16	22	24
Nominal	Cooling Capacity	kW	2.7	3.7	4.5	6.0	7.1
	Heating Capacity	kW	4.0	5.0	5.5	7.0	8.1
UK	Cooling Total/Sensible	kW	2.44/2.03	3.42/2.74	4.49/3.56	5.96/4.24	6.84/4.71
	Heating	kW	2.05	2.61	3.53	3.98	5.27
Cooling EN14825	Range Min. - Max.	kW	1.3 - 3.2	1.3 - 4.1	1.5 - 5.3	2.4 - 6.7	2.4 - 7.7
	Power Input	kW	0.035	0.035	0.030	0.040	0.043
Heating EN14825	Range Min. - Max.	kW	0.9 - 4.8	1.0 - 5.3	1.1 - 6.5	1.8 - 7.5	1.8 - 8.8
	Power Input	kW	0.040	0.040	0.035	0.040	0.043
Indoor Data							
Air Flow	High - Low	l/s	167 - 67	176 - 83	213 - 92	273 - 168	313 - 184
	High - Low	m ³ /h	600 - 240	636 - 300	768 - 330	984 - 606	1128 - 664
Sound	Pressure High - Low	dB(A)	39 - 24	39 - 24	43 - 26	46 - 34	48 - 35
	Power High - Low	dB(A)	54 - 39	54 - 39	58 - 41	61 - 51	63 - 50
Unit	Height x Width x Depth	mm	293 x 798 x 230	293 x 798 x 230	293 x 798 x 230	320 x 1050 x 250	320 x 1050 x 250
	Weight	kg	9	10	10	14	14
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	16/14	16/14	16/14	16/14	16/14
Remote Controller			WH-TA17NE	WH-TA17NE	WH-TA17NE	WH-TC09NE	WH-TC09NE

Accessories

RB-RXS30-E	Remote Controller Built-In Timer	Weekly-timer, single combination	
RB-N101S-G	WiFi Controller	WiFi adapter	
RB-N102S-G	WiFi Controller	WiFi adapter and cable	