

DIGITAL INVERTER

S U P E R
DIGITAL INVERTER



Triple-Split System Overview



Nominal Cooling Capacity	kW	10.0	12.5	14.0	20.0	23.0
Nominal Heating Capacity	kW	11.2	14.0	16.0	22.4	28.0
	hp	4	5	6	8	10

Outdoor Units	Digital Inverter Full Spec available	1 phase	RAV-GM1101ATP-E	RAV-GM1401ATP-E	RAV-SM1603AT-E1	
	Digital Inverter Full Spec available	3 phase	RAV-GM1101AT8P-E	RAV-GM1401AT8P-E		RAV-SM2246AT8-E RAV-SM2806AT8-E
	Super Digital Inverter Full Spec available	1 phase	RAV-GP1101AT-E	RAV-GP1401AT-E		
	Super Digital Inverter Full Spec available	3 phase	RAV-SP1104AT8-E1	RAV-SP1404AT8-E1	RAV-SP1604AT8-E1	

Triple-Split Indoor/Outdoor Combinations	High-Wall	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase	3 x RAV-RM301KRTP-E	3 x RAV-RM401KRTP-E	3 x RAV-RM561KRTP-E	3 x RAV-RM801KRTP-E	3 x RAV-RM801KRTP-E
	Compact Cassette	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase	3 x RAV-RM301MUT-E	3 x RAV-RM401MUT-E	3 x RAV-RM561MUT-E		
	4-Way Cassette	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase			3 x RAV-RM561UTP-E	3 x RAV-RM801UTP-E	3 x RAV-RM801UTP-E
	Slim Ducted	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase	3 x RAV-RM301SDT-E	3 x RAV-RM401SDT-E	3 x RAV-RM561SDT-E		
	Ducted	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase			3 x RAV-RM561BTP-E	3 x RAV-RM801BTP-E	3 x RAV-RM801BTP-E
	Ceiling Suspended	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase		3 x RAV-RM401CTP-E	3 x RAV-RM561CTP-E	3 x RAV-RM801CTP-E	3 x RAV-RM801CTP-E
	Floor-Mounted + RBC-CK2	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase		3 x MMF-AP0156H1-E	3 x MMF-AP0186H1-E	3 x MMF-AP0246H1-E	3 x MMF-AP0246H1-E
	Concealed-Chassis + RBC-CK1	DI 1 phase DI 3 phase SDI 1 phase SDI 3 phase	3 x MML-AP0094BH1-E	3 x MML-AP0124BH1-E	3 x MML-AP0184BH1-E	3 x MML-AP0244BH1-E	

The indoor unit prices shown are the total retail price for the 2, 3 or 4 indoor units required for that particular combination. The total retail price includes 1 x RBC-AMT32E remote controller and the branch pipe kit (triple systems only). Accessory price breakdown available on page 241 to page 246. If the outdoor units are used as part of a twin-split, then restrictions on pipe lengths apply. Please consult the technical manual for full technical specifications.