



Slim Ducted Indoor Unit

CODE		53	
Performance			
Indoor Unit		RAV-	RM561SDT-E
Outdoor Unit		RAV-	GP561ATP-E
Nominal	Cooling Capacity	kW	5.0
	Heating Capacity	kW	5.6
	EER/COP	W/W	3.21/3.54
UK	Cooling Total/Sensible	kW	4.8/3.6
	Heating	kW	3.55
Cooling EN14825	Range Min. - Max.	kW	1.2 - 5.6
	Power Input	kW	1.56
	Pdesign	kW	5.00
	SEER/Energy Efficiency Class		5.77/A+
	Seasonal Energy Consumption	kWh/a	303
Heating EN14825	Range Min. - Max.	kW	0.9 - 7.0
	Power Input	kW	1.58
	Pdesign	kW	3.80
	SCOP/Energy Efficiency Class		4.20/A+
	Seasonal Energy Consumption	kWh/a	1266
Indoor Data			
Air Flow	High - Medium - Low	l/s	217 - 188 - 162
	High - Medium - Low	m ³ /h	780 - 678 - 582
External Static Pressure	Standard (Upper - Lower)	Pa	29 (4 - 44)
Sound Pressure	High - Medium - Low	dB(A)	45 - 40 - 36
	High - Medium - Low (Under inlet)	dB(A)	48 - 46 - 43
Sound Power	High - Medium - Low	dB(A)	60 - 55 - 51
	High - Medium - Low (Under inlet)	dB(A)	60 - 55 - 51
Unit	Height x Width x Depth	mm	210 x 845 x 645
	Weight	kg	22
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Drain Pipe Connection OD/ID	mm	VP25 - VP25
	Lift Pump Drain Height from Unit Base	mm	< 850
Remote Controller			RBC-AMT32E
Outdoor Data			
Operating Range	Cooling/Heating	°C	-15 to 52/-27 to 15
Air Flow	High	m ³ /h - l/s	2250 - 625
Sound	Pressure High Cooling/Heating	dB(A)	46/48
	Power High Cooling/Heating	dB(A)	63/65
Unit	Height x Width x Depth	mm	630 x 799 x 299
	Weight	kg	45
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4
	Min.-Max. Length	m	3-50
	Maximum Height Difference	m	±30
	Drain Port Connection	mm	16
Refrigerant	Gas - Base Charge/Chargeless Length	kg/m	R32 - 1.35/20
	Additional Charge Liquid Side	g/m	20
Run Current	Maximum	A	7.81
Power Cable	Outdoor to Indoor		3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16

Accessories

RBC-AMS41E	Remote Controller Built-In Timer	Full control including service functions with fully-programmable 7-day timer
RBC-MTSC1	Mini Touch Screen Controller	Mini touch screen controller with configurable icons
RBC-AMS55E-ES	Remote Controller	Includes energy monitoring, timer and backlight display as well as power-save functions, multilingual
RBC-AS41E	Simplified Controller	Ideal for hotel and basic use applications (no service function available)
RBC-ASC11E	Compact Remote Controller	Simplified backlight display controller with timer off, multilingual
TCB-AX32E2	External Receiver	Independent receiver and WH-L11SE remote controller for all models
RBC-SMF1	Fan Interface	Interface to provide an output to enable an external fan from the unit
RBC-SMT1	CN02 Connector Timer Interface Lead	Lead to provide ON/OFF control from the RBC-AMT32E remote or any central controller
TCB-TC41LE	Remote Sensor	Room temperature sensing in conditioned space



Concealed false ceiling installation



Auto-diagnosis



Low ambient cooling to -15°C DB



Self-cleaning



Single-split



Chargeless



Automatic restart



Built-in drain pump



Wired controller

