



Triple-Split Slim Ducted Indoor Unit

CODE			100	100	125	125	140
Performance							
Indoor Unit 1	RAV-	RM301SDT-E	RM301SDT-E	RM401SDT-E	RM401SDT-E	RM561SDT-E	
Indoor Unit 2	RAV-	RM301SDT-E	RM301SDT-E	RM401SDT-E	RM401SDT-E	RM561SDT-E	
Indoor Unit 3	RAV-	RM301SDT-E	RM301SDT-E	RM401SDT-E	RM401SDT-E	RM561SDT-E	
Outdoor Unit	RAV-	GP1101AT-E	SP1104AT8-E1	GP1401AT-E	SP1404AT8-E1	SP1604AT8-E1	
Nominal	Cooling Capacity	kW	10.0	10.0	12.5	12.5	14.0
	Heating Capacity	kW	11.2	11.2	14.0	14.0	16.0
	EER/COP	W/W	3.91/4.19	3.58/4.19	3.5/3.86	3.24/3.81	2.81/3.48
UK	Cooling Total/Sensible	kW	9.60/7.20	9.70/7.40	-*	12.10/9.00	13.50/10.10
	Heating	kW	8.00	7.31	-*	9.14	10.45
Cooling EN14825	Range Min. - Max.	kW	3.1 - 12.0	2.6 - 12.0	3.1 - 14.0	2.6 - 14.0	2.6 - 16.0
	Power Input	kW	2.56	2.79	3.57	3.86	4.99
	Pdesign	kW	10.00	10.00	12.00	12.5	14.0
	SEER/Energy Efficiency Class		6.65/A++	5.55/A	-*	5.49/216.6	5.92/233.8
	Seasonal Energy Consumption	kWh/a	696	631	-*	-	-
Heating EN14825	Range Min. - Max.	kW	2.6 - 13.0	2.4 - 14.0	2.6 - 16.5	2.4 - 18.0	2.4 - 19.0
	Power Input	kW	2.67	2.67	3.63	3.67	4.60
	Pdesign	kW	7.60	11.60	8.00	11.8	12.0
	SCOP/Energy Efficiency Class		4.00/A+	3.84/A	-*	3.96/155.4	4.07/159.8
	Seasonal Energy Consumption	kWh/a	2569	4234	-*	-	-
Indoor Data							
Air Flow	High - Medium - Low	l/s	183 - 156 - 133	183 - 156 - 133	192 - 167 - 145	192 - 167 - 145	217 - 188 - 162
	High - Medium - Low	m ³ /h	660 - 560 - 480	660 - 560 - 480	690 - 600 - 522	690 - 600 - 522	780 - 678 - 582
External Static Pressure	Standard (Upper - Lower)	Pa	30 (5 - 45)	30 (5 - 45)	30 (5 - 45)	30 (5 - 45)	29 (4 - 44)
Sound Pressure	High - Medium - Low	dB(A)	39 - 36 - 33	39 - 36 - 33	39 - 36 - 33	39 - 36 - 33	45 - 40 - 36
	High - Medium - Low (Under inlet)	dB(A)	45 - 43 - 41	45 - 43 - 41	45 - 43 - 41	45 - 43 - 41	48 - 46 - 43
Sound Power	High - Medium - Low	dB(A)	54 - 51 - 48	54 - 51 - 48	54 - 51 - 48	54 - 51 - 48	60 - 55 - 51
	High - Medium - Low (Under inlet)	dB(A)	60 - 58 - 56	60 - 58 - 56	60 - 58 - 56	60 - 58 - 56	63 - 61 - 58
Unit	Height x Width x Depth	mm	210 x 845 x 645	210 x 845 x 645	210 x 845 x 645	210 x 845 x 645	210 x 845 x 645
	Weight	kg	22	22	22	22	22
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Height Difference Indoor To Indoor	m	±0.5	±0.5	±0.5	±0.5	±0.5
	Branch Kit (Sold Separately)		RBC-TRP100E	RBC-TRP100E	RBC-TRP100E	RBC-TRP100E	RBC-TRP100E
	Outdoor Connection To Distributor (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Sub Branch Line To Indoor (gas - liquid)	inch	3/8 - 1/4	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Max. Subtractive Separation Between Indoors	m	10	10	10	10	10
	Max. Length Distributor To Furthest Indoor	m	15	15	15	15	15
	Drain Pipe Connection Upper - Lower	mm	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25	VP25 - VP25
	Lift Pump Drain Height from Unit Base	mm	< 850	< 850	< 850	< 850	< 850
Power Cable	Indoor to Indoor		2 core + earth	2 core + earth	2 core + earth	2 core + earth	2 core + earth
Remote Controller			RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
Outdoor Data							
Operating Range	Cooling/Heating	°C	-15 to 52/-27 to 15	46 to -15/15 to -20	-15 to 52/-27 to 15	46 to -15/15 to -20	46 to -15/15 to -20
Air Flow	High	m ³ /h - l/s	6960 - 1933	6060 - 1683	6960 - 1933	6180 - 1717	6180 - 1717
Sound	Pressure High Cooling/Heating	dB(A)	49/50	49/50	50/51	51/52	51/53
	Power High Cooling/Heating	dB(A)	66/67	66/67	67/68	68/69	68/70
Unit	Height x Width x Depth	mm	1550 x 1010 x 370	1340 x 900 x 320	1550 x 1010 x 370	1340 x 900 x 320	1340 x 900 x 320
	Weight	kg	104	95	104	95	95
Pipe Connection	Flare Connections (gas - liquid)	inch	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Min.-Max. Length	m	3-50	3-50	3-50	3-50	3-50
	Maximum Height Difference	m	±30	±30	±30	±30	±30
	Drain Port Connection	mm	16	16	16	16	16
Refrigerant	Gas - Base Charge	kg	R32 - 3.1	R410A - 3.1	R32 - 3.1	R410A - 3.1	R410A - 3.1
	Additional Charge Main Liquid Side	g/m	35	40	35	40	40
	Additional Charge Sub Liquid Side	g/m	20	20	20	40	40
Run Current	Maximum	A	12.78	3.72	17.37	5.42	6.66
Power Cable	Outdoor to Header Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-20	380-415/3/50-10	220-240/1/50-25	380-415/3/50-16	380-415/3/50-16
* Waiting for published data.							

For Features and Accessories, please refer to the individual single-split system units.