



## Twin-Split Slim Ducted Indoor Unit

CODE		50	67	95	95	
<b>Performance</b>						
<b>Indoor Unit 1</b>		RAV-	RM301SDT-E	RM401SDT-E	RM561SDT-E	RM561SDT-E
<b>Indoor Unit 2</b>		RAV-	RM301SDT-E	RM401SDT-E	RM561SDT-E	RM561SDT-E
<b>Outdoor Unit</b>		RAV-	GM561ATP-E	GM801ATP-E	GM1101ATP-E	GM1101AT8P-E
Nominal	Cooling Capacity	kW	5.0	6.7	9.5	9.5
	Heating Capacity	kW	5.3	7.7	11.2	11.2
	EER/COP	W/W	2.73/3.27	2.82/3.32	3.14/3.75	3.14/3.75
UK	Cooling Total/Sensible	kW	4.80/3.30	-*	9.60/6.80	9.60/6.80
	Heating	kW	3.79	-*	8.01	8.01
Cooling EN14825	Range Min. - Max.	kW	1.5 - 5.6	1.5 - 7.4	3.0 - 11.2	3.0 - 11.2
	Power Input	kW	1.83	2.38	3.03	3.03
	Pdesign	kW	5.00	6.70	9.50	9.50
	SEER/Energy Efficiency Class		5.14/A	-*	5.32/A	5.32/A
	Seasonal Energy Consumption	kWh/a	346	-*	625	625
Heating EN14825	Range Min. - Max.	kW	1.5 - 6.3	1.5 - 9.0	3.0 - 13.0	3.0 - 13.0
	Power Input	kW	1.62	2.32	2.99	2.99
	Pdesign	kW	2.80	5.10	7.40	7.40
	SCOP/Energy Efficiency Class		4.16/A+	-*	4.19/A+	4.19/A+
	Seasonal Energy Consumption	kWh/a	1517	-*	2471	2471
<b>Indoor Data</b>						
Air Flow	High - Medium - Low	l/s	183 - 156 - 133	192 - 167 - 145	217 - 188 - 162	217 - 188 - 162
	High - Medium - Low	m <sup>3</sup> /h	660 - 560 - 480	690 - 600 - 522	780 - 678 - 582	780 - 678 - 582
External Static Pressure	Standard (Upper - Lower)	Pa	30 (5 - 45)	30 (5 - 45)	29 (4 - 44)	29 (4 - 44)
Sound Pressure	High - Medium - Low	dB(A)	39 - 36 - 33	39 - 36 - 33	45 - 40 - 36	45 - 40 - 36
	High - Medium - Low (Under inlet)	dB(A)	45 - 43 - 41	45 - 43 - 41	48 - 46 - 43	48 - 46 - 43
Sound Power	High - Medium - Low	dB(A)	54 - 51 - 48	54 - 51 - 48	60 - 55 - 51	60 - 55 - 51
	High - Medium - Low (Under inlet)	dB(A)	60 - 58 - 56	60 - 58 - 56	63 - 61 - 58	63 - 61 - 58
Unit	Height x Width x Depth	mm	210 x 845 x 645	210 x 845 x 645	210 x 845 x 645	210 x 845 x 645
	Weight	kg	22	22	22	22
Pipe Connection	Flare Connections (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Height Difference Indoor To Indoor	m	±0.5	±0.5	±0.5	±0.5
	Outdoor Connection To Distributor (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Sub Branch Line To Indoor (gas - liquid)	inch	3/8 - 1/4	1/2 - 1/4	1/2 - 1/4	1/2 - 1/4
	Max. Subtractive Separation Between Indoors	m	5	5	10	10
	Max. Length Distributor To Furthest Indoor	m	10	10	15	15
	Drain Pipe Connection Upper - Lower	mm	VP26/20	VP26/20	VP26/20	VP26/20
	Lift Pump Drain Height from Unit Base	mm	< 850	< 850	< 850	< 850
Power Cable	Indoor to Indoor		2 core + earth	2 core + earth	2 core + earth	2 core + earth
Remote Controller			RBC-AMT32E	RBC-AMT32E	RBC-AMT32E	RBC-AMT32E
<b>Outdoor Data</b>						
Operating Range	Cooling/Heating	°C	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15	-15 to 46/-15 to 15
Air Flow	High	m <sup>3</sup> /h - l/s	2400 - 667	2700 - 750	4080 - 1133	4080 - 1133
Sound	Pressure High Cooling/Heating	dB(A)	46/48	48/52	54/57	55/57
	Power High Cooling/Heating	dB(A)	63/65	65/69	70/74	70/74
Unit	Height x Width x Depth	mm	550 x 780 x 290	550 x 780 x 290	890 x 900 x 320	890 x 900 x 320
	Weight	kg	40	44	68	69
Pipe Connection	Flare Connections (gas - liquid)	inch	1/2 - 1/4	5/8 - 3/8	5/8 - 3/8	5/8 - 3/8
	Min.-Max. Length	m	5-30	5-30	5-50	5-50
	Maximum Height Difference	m	±30	±30	±30	±30
	Drain Port Connection	mm	16	16	16	16
Refrigerant	Gas - Base Charge	kg	R32 - 0.9	R32 - 1.3	R32 - 2.1	R32 - 2.1
	Additional Charge Main Liquid Side	g/m	20	35	35	35
	Additional Charge Sub Liquid Side	g/m	20	20	20	20
Run Current	Maximum	A	8.58	11.20	14.70	4.90
Power Cable	Outdoor to Header Indoor		3 core + earth	3 core + earth	3 core + earth	3 core + earth
Power Supply	Suggested Fuse Size	V/ph/Hz-A	220-240/1/50-16	220-240/1/50-16	220-240/1/50-20	380-415/3/50-10
* Waiting for published data.						

For Features and Accessories, please refer to the individual single-split system units.